



## **NOTES**

- 1. Where the space between ramps is less than 500mm, joined ramps shall be used.
- 2. In corner situations where the pavement in one street differs from the other, extend the use of the higher quality material around the corner and make a transition at the side of the ramp.
- 3. Ensure that the design of all ramps and the provision of tactile ground surface indicators (TGSI's) are in accordance with: Australian Standard AS1428 (all applicable parts).
- 4. All dimensions are in millimetres unless noted otherwise.

Top of bluestone kerb flush with bluestone channel invert	Top of bluestone kerb
	Bluestone channel invert
B SECTION	

		Disclaimer:
		The authors and sponsoring organisations shall have no liability or responsibility to the user or any
		other person or entity with respect to any liability, loss or damage caused or alleged to be caused, directly or indirectly, by the adoption and use of these Standard Drawings including, but not limited to.
		any interruption of service, loss of business or anticipatory profits, or consequential damages resulting
APPROVED FOR USE	DEC 2020	from the use of these Standard Drawings. Persons must not rely on these Standard Drawings as the equivalent of, or a substitute for, project-specific design and assessment by an appropriately qualified
Revision	Date	professional.



Approved	Project Services	DRESSED BLUESTONE KERB AND CHANNEL RAMP				
	Dec. 2020	Original Size	Drawing No:	CPP1401 Re	v:	F